ICU Series B-E-AC802





Key Features:

- 550 lbs (250 kg) weight capacity
- Standard fifth wheel for improved mobility
- 21" (53 cm) low height
- Storage area in base for two oxygen E-cylinder tanks and belongings
- Radiolucent fowler section
- Dual brake pedal mechanisms
- Adjustable knee gatch for enhanced comfort
- Fold-down siderails
- 8" (20 cm) wheel casters
- Pressure relief surfaces

Standard Features:

- LINAK[™] DC Actuators
- Modular battery backup
- LED night light
- Four IV pole sockets
- Four integrated roller bumpers
- Metal litter deck
- X-ray cassette holder
- CPR release system

- Trendelenburg and reverse Trendelenburg
- Patient controls on inner siderails
- Flat litter deck for compatibility with standard patient surfaces
- Adjustable bed height
- Adjustable foot extension
- Adjustable litter with chair position
- Integrated Digital Scale

- Patient Exit Alarm
- Scale and Fowler Angle Indicator
 on Siderail
- Foley Bag Holder
- Integrated push handles
- 5th wheel for improved mobility

The new Amico ICU bed features a versatile design suitable for a wide range of patients. The ICU bed is differentiated by its enhanced chair position as well as its ergonomic and robust design. This product truly helps provide a more meaningful level of care to patients.

This bed has a battery back-up system to enable motion even when the bed is disconnected or during patient transport. The ICU bed also features LINAK[™] DC actuators that offer a reliable yet silent motion for the bed's electromechanical system.

Technical Specifications



Model Number		B-E-AC802
Overall Dimensions		
Overall Length		
Retracted		83" (211 cm)
Extended		91" (231 cm)
Overall Width		
Siderails Up		42" (107 cm)
Siderails Down		38" (96.5 cm)
Patient Surface		
Retracted		32" x 71" (81 cm x 180 cm)
Extended		32" x 79" (81 cm x 201 cm)
Height Range (to the surfa	ace of the litter)	20"(06 E cm)
High Low		38" (96.5 cm) 20.5" (52 cm)
		20.5 (52 CH)
Litter Positioning		
Trendelenburg/Reverse Tr	endelenburg	± 18°
Backrest	C .	0° - 70°
Knee Gatch		0° - 21°
Weight Capacity & Caste	r Diameter	
Weight Capacity		550 lbs (250 kg)
Caster Diameter		6" (15 cm)
Electronics		
Volts		
Domestic		120 VAC
International		220 VAC
Ampere Rating		
Domestic		7.5 A
International		4.0 A
Current Leakage		<300 µA
Frequency		50-60 Hz
Hospital Grade Plug		Yes
ional Features & Acc	assarias:	
		Ded Fuit Al-
sure relief surfaces	Overbed table	Bed Exit Alarm
novable IV pole - 2 stage	Brake not set alarm	Fowler Angle In

• IV hook

Siderail covers

• Communication to nurse call systems • Oxygen tank holder

- Fowler Angle Indicator
- Hand pendant controls
- 3-Zone Bed Exit Alarm

Amico Beds Corporation reserves the right to change product specifications without notice.

Warranty: Three years parts

Amico Beds Corporation 85 Fulton Way, Richmond Hill, ON L4B 2N4, Canada | 600 Prime Place, Hauppauge, NY 11788, USA Toll Free Tel: 1.877.462.6426 | Toll Free Fax: 1.866.440.4986 | Tel: 905.764.0800 | Fax: 905.764.0862