

Lumex floor lifts are designed to provide safer and more secure transfers of patients by caregivers. Lumex lifts are very sturdy and easy to use.

- Heavy gauge steel construction with white powder-coated finish and rubber-coated low base legs protect furniture and walls
- Swan neck enables outstanding lifting range of 55.5"
- Six point spreader bar with 360° rotation accommodates 2-, 4-, or 6-point slings
- Large, easy to grip padded handles for easy maneuverability
- Powered high/low and base open/close simplifies operation
- Ergonomic hand pendant with hook
- Premium electronics with LCD display. Lift can be operated via the control box or the hand pendant
- Emergency stop button and manual lowering mechanism
- Alarm and visual indicator on control box and hand pendant for low battery charge (24V DC motor) or overload
- Battery may be charged while on the lift or remotely in charging caddy
- Spare battery and charging caddy included
- Durable twin wheel casters, 3" front, 4" rear braking
- Designed to meet the requirements of HCPCS Code E0635
- How-to-use video included



Optional digital scale DSC270



**Warranty:**

Frame and spreader bar three (3) year limited  
 Actuator two (2) year limited  
 Batteries one (1) year limited



Model	Floor Clearance	Spreader Bar Minimum Height from Sling Attachment	Spreader Bar Maximum Height from Sling Attachment	Overall Length	Minimum Base Width (outside)	Maximum Base Width (outside)	Safe Working Load (EVENLY DISTRIBUTED)	Product Weight
LF500	4.3"	19.3"	74.8"	49.2"	25.6"	39.4"	500 lb	116.8 lb